

OPTICUT C 50

A cross cut system for the future



OptiCut C 50 the convincing saw system

- **Low maintenance**
- **Reliable:** Approved technology made by WEINIG
- **Efficient:** Effortless cutting of small and mid-sized cross sections at high cutting frequency thanks to a powerful saw motor
- **Safe:** 2-hand control system, protection shield and downholders to assure highest safety standards



Product Unit Cutting / Gluing

WEINIG DIMTER GMBH & CO. KG

Rudolf-Diesel-Str. 14–16

89257 Illertissen

Germany

Phone +49 (0) 73 03 / 15-0

Fax +49 (0) 73 03 / 15-199

info-cutting@weinig.com


www.weinig.com

Wide range of accessories

- **Pneumatic protection shield:** Easy and quick access to the cutting area thanks to a lowerable shield to prevent manual intervention combined with a reduced space requirement
- **Workpiece feeding:** Exact and comfortable cross cutting thanks to infeed and outfeed rollerway tables and continuously variable pendulum stop devices
- **Positioning system:** Easy, quick and precise alignment and/or positioning of workpieces thanks to the automatic positioning system EasyStop

Saw diagram

Timber thickness in mm



Technical data

Capacity saw motor

5,5 kW / (7,5 kW)

Saw blade diameter

500 mm

Cross section range

min.	20 mm x 10 mm
max.	360 mm x 25 mm
	300 mm x 100 mm
or	(300 mm x 60 mm)
	(220 mm x 120 mm)

CE compliant, BG certified (German employer's liability insurance association)
(*) option