

CONTUREX ARTIS AND ARTIS⁺

Be quick and benefit from our offer!*

Benefit from our special offer for the 10-year Conturex anniversary with new additional function.



Technical details

- Width min./max. 40 - 260 mm
- Thickness min./max. 25 - 150 mm
- Length min./max. 175 - 3,500 mm (option: 175 - 4,500 mm)
- All six sides can be machined
- 290 mm long mandrels
- 12 kg tool weight
- 340 mm maximum diameter
- Slot depth up to 140 mm

Highlights


- Complete processing in one clamping for maximum precision
- **New PowerGrip clamping table RePos easy**
- High availability
- Processing without retooling, even for the smallest batches
- Automation enables less manpower in production
- Energy feedback modules means savings in energy

* Offer limited to 10 machines



CONTUREX ARTIS AND ARTIS⁺

Highlights



PowerGrip RePos easy

- Even more flexibility with slim profiles and new architect window systems
- Best surface quality thanks to the WEINIG RePos clamping system



Main spindle with 3 or 4-axis technology (optional)

- 30 kW (S6)
- Indirect drive protects the motor in critical situations



WEINIG Mech

- Multi-stage expansion of mechanization systems
- For reliable unmanned production



WEINIG CAM

- Full 3D CAD / CAM system for custom design
- Simple and fast programming



WEINIG Sim

- More comfort and safety through visualization of the production data
- Collision control through simulation



WEINIG solid WF

- From the idea to the finished workpiece



Product Window/CNC

MICHAEL WEINIG AG
Weinigstraße 2/4
97941 Tauberbischofsheim
Germany

Phone +49 9341 86-0
Fax +49 9341 7080
info-window@weinig.com
www.weinig.com